



US005709976A

**United States Patent** [19]**Malhotra**[11] **Patent Number:** **5,709,976**[45] **Date of Patent:** **Jan. 20, 1998**[54] **COATED PAPERS**[75] **Inventor:** **Shadi L. Malhotra**, Mississauga,  
Canada[73] **Assignee:** **Xerox Corporation**, Stamford, Conn.[21] **Appl. No.:** **656,814**[22] **Filed:** **Jun. 3, 1996**[51] **Int. Cl.<sup>6</sup>** ..... **B41M 5/00; B41J 2/01**[52] **U.S. Cl.** ..... **430/124; 347/105; 428/195;**  
428/211; 428/215; 428/216; 428/423.1;  
428/481; 428/484; 428/488.1; 428/511;  
428/521; 428/522; 430/126[58] **Field of Search** ..... 428/195, 211,  
428/215, 216, 423.1, 481, 484, 488.1, 511,  
521, 522; 347/105; 430/124, 126[56] **References Cited****U.S. PATENT DOCUMENTS**

4,734,336	3/1988	Oliver et al.	428/537.5
5,053,268	10/1991	Ehara et al.	428/215
5,223,338	6/1993	Malhotra	428/342
5,302,249	4/1994	Malhotra et al.	162/135
5,457,486	10/1995	Malhotra et al.	347/105
5,472,757	12/1995	Ogawa et al.	428/195

*Primary Examiner*—Pamela R. Schwartz*Attorney, Agent, or Firm*—E. O. Palazzo[57] **ABSTRACT**

Disclosed is a coated paper which comprises (a) a substrate; (b) a hydrophobic barrier layer comprised of a water insoluble component and a water or alcohol soluble anticurl agent, said hydrophobic barrier layer being present on both sides of the substrate; (c) image receiving coatings situated on the top of both hydrophobic barrier layers, said image receiving coatings being suitable for receiving images of an aqueous ink, said coatings comprising (1) a polymeric binder, (2) a dye fixative, (3) a pigment, (4) a lightfastness inducing agent, and (5) a biocide. In another embodiment, the present invention is directed to a coated paper which comprises (a) a substrate; (b) a hydrophobic barrier layer comprised of a water insoluble component, and a water or alcohol soluble anticurl agent, said hydrophobic barrier layer being present on both sides of the substrate; (c) image receiving coatings situated on the top of both hydrophobic barrier layers, said image receiving coatings being suitable for receiving images developed with electrostatic toner compositions, said coatings comprising (1) a polymeric binder, (2) an antistatic agent, (3) a lightfastness inducing agent, (4) a pigment, and (5) an optional biocide.

**27 Claims, No Drawings**